

Model 1200LB



1200 lbs Single Magnetic Lock with Bond Sensor, Door Status Sensor and Status LED

Specifications

- 1200 lbs holding force
- Magnet size: 10-1/2" L x 2-7/8" H x 1-1/2" W
- Armature size: 7-3/8" L x 2-3/8" H x 9/16" W
- Operates on 12 or 24 VDC, selectable
- Low current draw: 400 mA at 12 VDC, 200 mA at 24 VDC
- Operating temperature: +14 to +131F [-10 to +55C]
- Sensors have SPDT 3A relay contacts

- E-Z mount system, no special tools required
- Non-aluminum parts are plated to resist corrosion
- Limited lifetime warranty

Options

- Clear anodized (US28) finish standard
- Duranodic (US40) finish available

Certifications & Listings

- UL 10C fire rated
- CAN4-S104 (ULC-S104) fire door conformant
- ULC-S527 listed
- UL 864 listed

Models

1200LB

1200 lbs Single Door Magnetic Lock with status LED, Bond Sensor and Door Status Sensor, 12 or 24 VDC, UL 10C and Canadian UL Listed

1200LBDURO

1200 lbs Single Door Magnetic Lock with status LED, Bond Sensor and Door Status Sensor, 12 or 24 VDC, US 40 Duranodic Finish, UL 10C and Canadian UL Listed

Features

- Bond sensor and door status sensor signal a powered and securely locked door
- Self drilling TEC screws
- Built-in arc suppression
- Instant release, no hysteresis

ALARMCONTROLS



ASSA ABLOY