

# Model 600D



## 600 lbs Double Magnetic Lock

### Specifications

- 600 lbs holding force per leaf
- Magnet size: 19-3/4" L x 1-7/8" H x 1" W
- Armature size: 7-1/4" L x 1-1/2" H x 5/8" W
- Operates on 12 or 24 VDC, selectable
- Low current draw: 400 mA at 12 VDC, 200 mA at 24 VDC
- Operating Temperature: +14 to +131F [-10 to +55C]

### Features

- Instant release, no hysteresis
- Non-aluminum parts are plated to resist corrosion
- Built-in arc suppression
- Can be used with any access control system
- E-Z mount system, no special tools required
- Self drilling TEC screws
- Limited lifetime warranty

### Options

- Clear anodized (US28) finish standard
- Duranodic (US40) finish available
- Dress covers in polished chrome and brass are available

### Certifications & Listings

- UL 10C fire rated
- CAN4-S104 (ULC-S104) fire door conformant

### Models

#### 600D

600 lbs Double Door Magnetic Lock, 12 or 24 VDC, UL 10C and Canadian UL Listed

#### 600DDURO

600 lbs Double Door Magnetic Lock, 12 or 24 VDC, US 40 Duranodic Finish, UL 10C and Canadian UL Listed

# ALARMCONTROLS



**ASSA ABLOY**