

**DynaLock Corporation**

705 Emmett Street

Bristol, CT 06010

Phone: 860.582.4761 • **Fax:** 860.585.0338**Email:** info@dynalock.com • **Website:** www.dynalock.com**7075 Series Break Glass Exit Stations**

Break glass assembly provides auxiliary method of releasing egress doors in an emergency situation. The assembly may be ordered in three versions: standard, standard with LED indicator or standard with audible.

Size: 6-3/4" x 4-1/2"

Contacts: SPDT-DB (FORM Z), MOM rated 6 Amps at 125VAC

Furnished with 5 spare glass lenses.

Results 1 - 5 of 5

<u>Item #</u>	<u>Item Name</u>	<u>Contact Ratings</u>
<u>7075</u>	Break Glass Exit Stations, Standard	SPDT-DB (FORM Z), MOM rated 6 Amps at 125 VAC
<u>7076</u>	Break Glass Exit Stations, with Bi-Color LED, Red/Green, 12/24VDC	SPDT-DB (FORM Z), MOM rated 6 Amps at 125 VAC
<u>7077</u>	Break Glass Exit Stations, with Audible Sounder, 1-28VDC, 1-28VDC	SPDT-DB (FORM Z), MOM rated 6 Amps at 125 VAC
<u>7078</u>	Spare Contact Block, SPDT	SPDT-DB (FORM Z), MOM rated 6 Amps at 125 VAC
<u>7079</u>	Spare Lenses, 5 Pk.	SPDT-DB (FORM Z), MOM rated 6 Amps at 125 VAC

Results 1 - 5 of 5