



Meets ANSI/BHMA 156.16, L11241.

### FS9 Floor Stop & Semi-Automatic Holder

- Semi-automatic floor-mounted holders accommodates with door to floor clearance of 1-1/2" or less.
- Cast from heavy-duty brass.
- Activate holder by flipping the engagement tongue forward. When door is opened, the hook (mounted on door) engages the tongue. To release, push firmly on door to disengage tongue.
- Universal screw pack accommodates all types of floor and door construction.

#### Dimensions

Overall Height: 3-1/2"

Base Dimensions: 2" wide x 3-1/2" long

#### Finishes

Ives Number	US3	US4	US10	US10B	US26	US26D
BHMA	605	606	612	613	625	626



Meets ANSI/BHMA 156.16, L11301

### FS40 Floor Stop & Automatic Holder FS41 FS42 FS43

- Automatic door holders ideal for heavy-traffic situations that require a simple, fool-proof, Hold-Open device.
- Forged from brass.
- Unit is activated automatically when door is opened. A firm pull on door releases the mechanism.
- Strikes accommodate different door to floor clearances.
- Model numbers are determined by strike/door-to-floor clearances.
- Holder position on door is adjustable.
- Universal screw pack allows for installation in all types of door construction.

#### Dimensions

Door to Floor Clearance:	FS40	FS41	FS42	FS43
	1/2" or less	9/16" to 1-1/16"	1-1/8" to 1-9/16"	1-5/8" to 2-1/16"

Holder Dimensions: 3" Wide x 3-11/16" High

#### Finishes *brass*

Ives Number	US3	US4	US10	US10B	US26	US26D
BHMA	605	606	612	613	625	626

