



FS446
Meets ANSI/BHMA 156.16, L11371 for brass and L31371 for aluminum.

FS450
Meets ANSI/BHMA 156.16, L11361 for brass and L31371 for aluminum.

FS446 Floor Stop & Manual Door Holder

FS450 Floor Stop & Manual Door Holder

- Manual type floor holder ideal for interior or exterior use.
- Cast brass or aluminum construction.
- Accommodates door undercut up to 2-1/2".
- Replaceable non-marring rubber tip.
- Unit functions as a stop but serves as a Hold-Open device when hook is manually engaged in strike. Unit requires manual disengagement to release Hold-Open.

FS446 packed with expansion shield and lead shield, for masonry type mounting

FS450 packed with 3 wood screws, for drywall mounting.

Dimensions

Overall Height: 3-3/4"

Height from Floor to Stop Center Line: 2-5/8"

Stop Diameter: 1-1/16"

Base Diameter: 2-1/12"

Finishes *brass*

Ives Number	US3	US4	US10	US10B	US15	US26	US26D
BHMA	605	606	612	613	619	625	626

Finishes *aluminum*

Ives Number	US28
BHMA	628



FS495 shown

FS495 Meets ANSI/BHMA 156.16, L11291 for brass

FS496 Meets ANSI/BHMA 156.16, L11301 for brass

FS497 Meets ANSI/BHMA 156.16, L11301 for brass

FS495 Wall Stop & Automatic Holder

FS496 Floor Stop & Automatic Holder

FS497 Floor Stop & Automatic Holder

- Automatic door holders ideal for heavy-traffic situations that require a simple, Hold-Open device.
- Cast brass construction.
- Recommended installation is holder on door and strike on wall.
- Holder position on door is adjustable.
- Holder is tapered to prevent "child riding."

Dimensions

FS495 Holds door 3-3/4" from wall.

FS496 Door to Floor Clearances 3/8" Maximum.

FS497 Door to Floor Clearances 1" Maximum.

Finishes *brass*

Ives Number	US3	US4*	US10	US10B	US26	US26D
BHMA	605	606	612	613	625	626

* not available on FS496, FS497.