Surface Bolts



1630 meets ANSI/BHMA A156.16, L84161 and UL listed 3 hour fire doors up to 8'0" in height.

1640 meets ANSI/BHMA A156.16, L24161.



UL listed 3 hour fire doors up to 8'0" in height.

SB1600Surface Bolt

- Standard Surface Bolt has 1" throw for maximum security.
- Ideal for all types of doors.
- Fully concealed mounting prevents vandalism.
- Available in locking version. Unit locks in both the up and down position. Locking Bolts are furnished with 2 keys in 4 keying variations.
- Units packed with wood and machine screws to meet most field conditions.
- Units available with either a universal top strike (T) or a flat bottom strike (B).
- 1630 Series is constructed of heavy duty steel.
- 1640 Series is constructed of brass.
- Optional sex bolts available

Dimensions

Body: 8" Long x 7/8" Wide x 3/4" Thick, Overall Knob or Lock Housing Projection: 1-1/2" Top Strike: 1-1/4" Wide x 7/8" Tall x 15/16" Deep Bottom Strike: 3" Long x 1" Wide x 1/8" Thick

SB1630 Finishes steel

SR1640 Finishes brass

32.0.10.1.11.31.03 27.033							
Ives Number	US3	US10B	US26D				
BHMA	605	613	626				

SB1600M1 SB1600M2 Surface Bolt

- Standard Surface Bolt has 3-1/2" throw for maximum security and for doors with larger undercuts.
- Sleek handle design.
- Ideal for all types of doors.
- Fully concealed mounting prevents vandalism.
- Available in locking version. Unit locks in both the up and down position. Locking bolts are furnished with 2 keys in 4 keying variations.
- Units packed with wood and machine screws to meet most field conditions.
- Units available with either a universal top strike (T) or a flat bottom strike (B).
- Constructed of heavy duty steel.
- Optional sex bolts available

Dimensions

Bar: 11" Long x 3/4" Wide x 3/4" Thick, locking version 1-1/2" Thick

Top Strike: 1-1/4" Wide x 7/8" Tall x 15/16" Deep Bottom Strike: 3" Long x 1" Wide x 1/8" Thick

Finishes

I IIIISIICS						
Ives Number	SP4	SP10	SP28	SP313	SPBLK	
RHMΔ	706	691	689	695	622	