





WS11 Meets ANSI/BHMA 156.16, L12011

WS11X Meets ANSI/BHMA 156.16, L12021

WS11 Wall Stops

- · Constructed in heavy duty cast brass.
- Hexagon section on unit aids in fastening unit when expansion shield is used.
- Replaceable rubber bumpers features off-set shoulder and threaded shank that screws into body of unit.

WS11 is furnished with wood screws for drywall mounting. WS11X is furnished with a threaded stud and expansion shield for masonry type mounting.

Dimensions

Base Diameter: 2"

Overall Projection: 3-3/4"

Finishes brass

Ives Number	US3	US4	US10	US10B	US26	US26D	
BHMA	605	606	612	613	625	626	





WS20X Meets ANSI/BHMA 156.16, L11351 for brass and L31351 for aluminum



WS20 WS20X Manual Wall Holders

- Constructed in cast brass or aluminum.
- Replaceable rubber bumpers feature off-set shoulder and threaded shank that screws into body of holder.
- · Hinged strike furnished matches body material and finish.

WS20 is furnished wood screws for drywall mounting. WS20X is furnished with threaded stud and expansion shield for masonry type mounting.

Dimensions

Base Diameter: 2-3/8"

Overall Projection: 4"

Strike Height: 2"

Strike Width: 1"

Finishes brass

Ives Number	US3	US4	US10	US10B	US26	US26D	
BHMA	605	606	612	613	625	626	

Finishes aluminum

i iiiisiies atominom					
Ives Number	US28				
ВНМА	628				