


## 400 Series Electromechanical Locks



**442S**

**405 PowerBolt**

**406S PowerBolt**

### **442S Cabinet Lock**

The 442S is a fail secure, solenoid driven cabinet lock. It can be mounted horizontally or vertically to control access to a cabinet. The 442S can be controlled by any kind of access control system that provides a dry contact output. Its small size and versatile mounting position make it ideal for many applications for controlling access to a small opening.

A battery powered (443BP) cabinet lock is also available.

### **405 PowerBolt**

The 405 PowerBolt is a mortise, right angle deadbolt with a 3/4" bolt and a 3/4" throw. It is available fail safe (standard) or fail secure (405S). Additional applications include top and bottom rail doors and all glass doors with the HDB405 herculite door bracket for 1/2" or 3/4" glass doors with no top rail.

### **406S PowerBolt**

The 406S PowerBolt is a fail secure, mortise right angle deadbolt with a 3/4" bolt and 3/4" throw.

## 400 Series Electromechanical Locks

### How To Order 400 Series Electromechanical Locks

405 – DBS – HDB405

Select Model

Select Option

Select Accessories

### 1. Select Model

#### PowerBolts

- 405** Rectangular Front, Fail Safe
- 405S** Rectangular Front, Fail Secure
- 406S** Rectangular Front, Fail Secure

#### Cabinet Locks

- 442S** Fail Secure

Fail Secure Lock – Requires power to unlock

Fail Safe Lock – Requires power to lock

### 2. Select Options

#### PowerBolts

- ARSB** Auto Relock Switch (ball type mechanical)  
1A @ 120VAC or 28VDC
- ARSM** Auto Relock Switch (Magnetic type)  
200mA @ 12 VAC/VDC  
100mA @ 24 VAC/VDC
- BPS** Bolt Position Switch  
SPDT 7A @ 250VAC
- DSB** Door Status Switch (Ball type mechanical)  
SPDT 1A @ 120 VAC or 28 VDC
- DSM** Door Status Monitor (magnetic type)
- RC1** Rectifier with filter (for AC voltage operation)  
Input: 12/24VAC  
Output: 1A @ 12/24 VDC

*Note: Ball type mechanical options cannot be ordered with magnetic type options.*

#### Cabinet Lock

- RCP** Rectifier (external module) for 442S only

### 3. Select Accessories

- HDB405** U bracket for 1/2" or 3/4" glass door  
(for 405, 405S only)
- MT** Mounting tabs (for 405, 405S only)



#### Specifications:

##### PowerBolts

- Input Voltage:** 12/24 VDC  
Dual voltage, field selectable
- Current Draw:** .9A @ 12VDC  
.45A @ 24VDC

##### 405/405S

- Bolt Size** 3/4" diameter  
3/4" throw
- Overall Size\*** 8" x 1 1/2" x 1 5/8"

##### 406

- Bolt Size** 3/4" diameter  
3/4" throw
- Overall Size\*** 10" x 1 1/2" x 1 5/8"
- \*Depth from face of plate

##### Cabinet Lock 442S

- Input Voltage:** 12/24VDC  
Dual Voltage, field selectable
- Current Draw:** .5A @ 12VDC  
.25A @ 24VDC

##### 442S

- Overall Size** 3" x 1" x 1"