

DPS

Door Position Switches

DPS-W and DPS-M door position switches enable access control systems to monitor the open or closed state of a door. These switches can transmit an initiate signal to Securitron's XDT delayed exit logic timers and DPA door prop logic timers.



DPS-W

Concealed Door Position Switch for Wood Doors:

- Mated magnetic switch and cylindrical magnetic contact
- Recesses into door and frame
- 3/4" [19mm] round installation, 15/16" deep
- Provides Normally Closed SPST switch
- Works with door gap up to 3/4" [18mm]
- MagnaCare® lifetime replacement, no fault warranty

PRODUCT OPTIONS

- Available in white, gray or black

DPS-M

Concealed Door Position Switch for Metal Doors:

- Mated magnetic switch and magnetic contact
- Recessed into door and frame
- 3/4" [19mm] round installation, 1/2" deep
- Larger cylindrical magnet counters shielding effect of steel
- Provides Normally Closed SPST switch
- Works with door gap up to 3/4" [18mm]
- MagnaCare® lifetime replacement, no fault warranty

SPECIFICATIONS

Electrical:

Switching Current AC/DC (max): 0.4A

Operating Temperature:

-40 to +150F [-40 to +65C]

» MODELS

PART # | Description

DPS-M-BK	DPS for Metal Doors - Black
DPS-M-GY	DPS for Metal Doors - Grey
DPS-M-WH	DPS for Metal Doors - White
DPS-W-BK	DPS for Wood Doors - Black
DPS-W-GY	DPS for Wood Doors - Grey
DPS-W-WH	DPS for Wood Doors - White



DPA

Door Prop Alarm

The DPA complements door position/door state detection with timed logic and relays that provide escalating alerts when a door is held, propped or unsecure after a defined time period. This unit promotes safety and loss prevention at ancillary exits for healthcare, commercial and retail facilities, and dorms.



PRODUCT FEATURES

- Multi-functional control timer provides relay action for alarms and alerts
- Monitors whether a door remains open after a defined time frame
- Includes three 5A SPDT outputs providing local and remote signaling
- Digital time settings from 30 to 240 seconds
- Detects attempts to tamper with lock or door status
- Multiple time ranges for escalating alerts

- Bypass mode for valid access/egress needs
- Comes with Piezo sounder and LED
- MagnaCare® lifetime replacement, no fault warranty

SPECIFICATIONS

Electrical:

Max draw 100 mA at 12 VDC
Max draw 50 mA at 24 VDC

Operating Temperature:

+32 to +120F [0 to +49C]

Shipping Weight:

2.05 lbs [0.93kg]

» MODELS

PART # | Description

BA-DPA-12	Door Prop Alarm Timer - 12 VDC w/ Boxed Alarm
BA-DPA-24	Door Prop Alarm Timer - 24 VDC w/ Boxed Alarm



SECURITRON
ASSA ABLOY