

# 00 Series



## FEATURES

- Durability - 500,000 Life Cycles
- Holding Force - 1000 lbs
- Only 1 Moving Part in Locking Mechanism
- Non-Handed Operation
- Heavy Duty Latch Spring
- Fail Secure-Standard Action (Unlocks with Power)

Voltage	Amps	Ohms	Sound	Duty	Wire Color
8-16VAC/4-6VDC	1.3-2.7	1.4	Buzz	Intermittent	Black
12VDC	0.40	30.0	Silent	Continuous	Red/White
24VAC	1.40	4.7	Buzz	Intermittent	Red
24VDC	0.19	125.0	Silent	Continuous	Black/White



### 001

For use in new or replacement installations in wood and metal jambs. For use with locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 5-7/8" x 1-1/4" – Mortise Backset 1-9/16" – Cavity Depth 1/2" – Cavity Width 9/16" – Cavity Height 1-1/2"

**001**  
(Brass Powder Coated)  
**001C**  
(Satin Chrome – BHMA651)

**RS** (Fail Safe)  
- For DC Models only.



### 002

For use in new or replacement installations in wood and metal jambs Auxiliary lever ramps for use with locksets which contain dead locking levers. Use with locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 7-15/16" x 1-7/16" – Auxiliary Ramp 2-7/8" – Mortise Backset 1-9/16" – Cavity Depth 1/2" – Cavity Width 9/16" – Cavity Height 1-1/2"

**002**  
(Aluminum Powder Coated)  
**002DB**  
(Dark Bronze Powder Coated)

**RS** (Fail Safe)  
- For DC Models only.



### 003

For surface mount installations on wood or metal jambs for in swinging applications with surface mount. Use with locksets and night latches having up to 5/8" throw, based on 1/8" door gap. When mounted on a pair of doors, strike is mounted to the inactive leaf.

Surface Mount – Case 4-11/16" x 1-1/4" – Cavity Depth 1/2" – Cavity Width 9/16" – Cavity Height 1-1/2"

**003**  
(Grey Moulded Cover)

**RS** (Fail Safe)  
- For DC Models only.



### 004

For new or replacement installations in wood jambs. Use with locksets with individual dead bolts. **Dead bolts cannot be released electrically.** Use with locksets having up to 5/8" throw, based on 1/8" door gap.

Face Plate 6-1/4" x 1-3/8" – Dead bolt Knockouts Top & Bottom 1-11/16" x 9/16" – Mortise Backset 2-3/4" – Cavity Depth 1/2" – Cavity Width 9/16" – Cavity Height 1-1/2"

**004**  
(Brass Powder Coated)  
**004C**  
(Satin Chrome – BHMA651)  
**004DB**  
(Dark Bronze Powder Coated)

**RS** (Fail Safe)  
- For DC Models only.

# Light Commercial Electric Strikes

# 00 Series

Light  
Commercial Strikes



## 005

For use in replacement installations in wood jambs and iron gates. Use with bored cylindrical locksets having up to 5/8" throw, based on 1/8" door gap.

**Face Plate** 3-1/2" x 1-3/8" – **Mortise Backset** 2-3/4" – **Cavity Depth** 1/2" – **Cavity Width** 9/16" – **Cavity Height** 1-1/2"

**005**  
(Brass Powder Coated)  
**005C**  
(Satin Chrome – BHMA651)

**RS** (Fail Safe)  
- For DC Models only.



## HD005

**Screwed-on Faceplate and reinforced Latch Pin provide additional strength for HEAVY DUTY installations.**

For use in replacement installations in wood jambs and iron gates. Use with bored cylindrical locksets having up to 5/8" throw, based on 1/8" door gap.

**Face Plate** 3-1/2" x 1-3/8" – **Mortise Backset** 2-3/4" – **Cavity Depth** 1/2" – **Cavity Width** 9/16" – **Cavity Height** 1-1/2"

**HD005**  
(Brass Powder Coated)  
**HD005C**  
(Satin Chrome – BHMA651)

**RS** (Fail Safe)  
- For DC Models only.



## S005

For use in replacement installations in wood jambs and iron gates. Use with bored cylindrical locksets having up to 3/4" throw, based on 1/8" door gap.

**Face Plate** 3-1/2" x 1-3/8" – **Mortise Backset** 2-7/8" – **Cavity Depth** 5/8" – **Cavity Width** 23/32" – **Cavity Height** 1-1/2"

**S005**  
(Brass Powder Coated)  
**S005C**  
(Satin Chrome – BHMA651)

**RS** (Fail Safe)  
- For DC Models only.



## 006

For surface mount installations on metal or wood jambs, for in swinging applications. Use with locksets or night latches having up to 5/8" throw, based on 1/8" door gap. When mounted on a pair of doors, strike is mounted to the inactive leaf.

**Case** 2-1/8" x 1-3/16" – **Surface Mounted** – **Die Cast Housing** – **Cavity Depth** 1/2" – **Cavity Width** 1/2" – **Cavity Height** 1-3/8"

**006**  
(Brass Powder Coated)

**RS** (Fail Safe)  
- For DC Models only.



## 007

For use in new or replacement installations in wood jambs. Use with locksets having up to 3/4" throw, based on 1/8" door gap.

**Face Plate** 4-7/8" x 1-1/4" – **Mortise Backset** 2-7/8" – **Cavity Depth** 5/8" – **Cavity Width** 3/4" – **Cavity Height** 1-1/2"

**007**  
(Brass Powder Coated)  
**007C**  
(Satin Chrome – BHMA651)

**RS** (Fail Safe)  
- For DC Models only.