



Industries, Inc.

Designer and Manufacturer of **AccessAbility**. Automatic Door Activation Solutions

4R SERIES (4-1/2" Round) Short Form Specifications

4-1/2 inch Round Automatic Door Activation switch by Wikk Industries, Inc.

Features: Smooth Rounded Corners, high quality images and text, tamper resistant by reason of no visible mounting screws.

Size: 4-1/2" (114 mm) round cover plate

Logo: Debossed or Engraved with infill colors as shown in literature, or custom Engraved and infilled with your choice of colors-Blue, Black, White, Red, Green and Chocolate Brown.

Material: Type 304 Stainless Steel in brushed finish US32D (630)

Optional Materials/Finishes: US32 (629), US3 (605), US4 (606), and US10B (613)

Switch Mechanism: UL® & CSA tested momentary SPDT snap action switch rated at 15 Amp 125/250 VAC

Mounting Plate: 1/8" thick Aluminum

Mounting:

Flush mount: single or double gang electrical boxes

Wikk product **N4RF** (Black ABS material)

Surface mount: Wikk's products-

WKS-4 US32D (630), US32 (629), US3 (605), US4 (606) and US10B (613)

WKS-4RF (Black ABS material), **N4RS** (Black ABS material),

SURF 4R (Brown phenolic material with adapter plate)

2x4 Box Sleeve in Satin Stainless Steel US32D (630) and Mirror US32 (629)

Switch projection from mounting surface: approximately 9/16" (14.2 mm)

WR (Weather Resistant) option: Rubber dome seal protects switch mechanism to effectively block dirt and moisture from damaging snap action switch.

Specified in:

MasterFormat® 1995: Section 08 710 Door Hardware

MasterFormat® 2004: Section 08 7120 Automatic Door Controls

From 4SPECS website: Section 08 7120 Door Controllers and Operators

CSI 3- Part Format Guide Specifications are available for download on the

Wikk's Website: <http://www.wikk.com>

Exclusive
Manufacturer of
the
INGRESS'R®



36" inches of
enlightened access
for
automatic doors