

rim

2100(F)

The 2100(F) is a rim exit device to be used with single doors or pairs of doors constructed of metal, wood or composite materials. The 2100(F) can be paired with a wide variety of trims to meet many applications.



certification/compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware
GXHX/GXHX7 - Fire exit hardware (F)
(4' x 8' single, 8' x 8' pairs, 3 hr.)
ZHEM - Latching hardware
ZHLA - Windstorm rated assemblies

ANSI/BHMA Certified: A156.3 Type 1, Grade 1



features

- Designed for wide stile doors
- Non-handed for easy installation
- Steel interlock "E" bracket maintains door-to-mullion relationship in fire-labeled devices
- Deadlocking pullman latchbolt positively engages roller strike
- Available certified hurricane resistant (refer to local codes). Specify 2100(F)WS



Hurricane

applications

- Single swing doors
- Pairs of doors (mullion required)
- Metal, wood or composite door materials

specifications

Door Opening Width:	-36 for 30" - 36" (76cm - 91cm) doors -42 for 36" - 42" (91cm - 107cm) doors -48 for 42" - 48" (107cm - 122cm) doors
Door Thickness:	1-3/4" (44mm) standard. Optional door thicknesses available to 4-1/2"; specify door thickness when ordering.
Minimum Stile Width:	4-1/2" (114mm)
Projection:	2-1/2" (64mm) active, 1-3/4" (44mm) depressed
Latchbolt:	3/4" (19mm) deadlocking stainless steel pullman-type
Strike:	757F, 793 optional (double door application, panic only)
Fasteners:	Machine screws and wood door fasteners standard for panic hardware. Sex nuts and bolts supplied standard for fire exit hardware.
Trims:	121NL cylinder only, 210F series utility trim, 440F series rose trim, 580F series rose trim with escutcheon plate, 620F series escutcheon trim, 630F series pull/thumbpiece trim. See pages 13-15.
Dogging:	Hex key dogging supplied standard on panic devices
Finishes:	613E, 630, 689, 691, 693, 695
Options:	Shim kit #223, sex nuts and bolts, MicroShield®
Warranty:	3-year limited