

rim

7200

The 7200 is a narrow stile rim exit device compatible with the aesthetics and functional requirements of contemporary doors. The 7200 comes in varied finishes and can be combined with a variety of trims to match any desired style.



certification/compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware

ANSI/BHMA Certified: A156.3, Type 4, Grade 1



features

- Designed for narrow stile doors
- 3/4" throw deadlocking stainless steel pullman latch
- Non-handed for easy installation

applications

- Single swing narrow stile doors
- Pairs of narrow stile doors with removable mullions
- Metal and aluminum doors
- For panic-rated doors only

specifications

Door Opening Width:	-24 for 24" (60cm) doors -36 for 30" - 36" (76cm - 91cm) doors -48 for 36" - 48" (91cm - 122cm) doors Optional sizes can be special ordered. Consult Technical Product Support.
Door Thickness:	1-3/4" (44mm) standard. 2" (51mm) and 2-1/4" (57mm); specify when ordering.
Minimum Stile Width:	2" (51mm)
Projection:	3-1/4" (83mm) active, 2-3/4" (70mm) dogged
Latchbolt:	3/4" (19mm) deadlocking stainless steel pullman type.
Strike:	Standard: 759. Optional: 793 (double door applications, panic only)
Fasteners:	Machine screws standard for panic hardware
Trims:	500F series escutcheon trim, 510F series pull/thumbpiece trim, 480F series offset pull trim. 121NL cylinder only trim. See pages 30-31.
Dogging:	Hex key dogging supplied standard
Options:	Cylinder dogging, shim kit #723NS, sex nuts and bolts, MicroShield®, Lumi-Lite®
Warranty:	5-year limited